



**FOOTNOTES:**

- 1) Due to manufacturing tolerances and continual product improvement, this specification can be subject to variance of + or - 3%. Dimensions listed are for power base only. Overall measurements will vary based on seating and accessory selections.
- 2) Without front riggings.
- 3) Varies with user weight, terrain, battery type, battery condition and tire pressure.
- 4) With rear caster suspension.
- 5) Base weight does not include seat or battery weights.
- 6) Standard high-back seat weight is 42.5 lbs.
- 7) Tested in accordance with ANSI/RESNA, WC Vol. 2, Section 4, & ISO 71764 standards. Results derived from theoretical calculations based on battery specifications and drive system performance. Testing conducted at maximum weight capacities. This specification can be subject to a variance of +10%, -5%.
- 8) 200 lbs. weight capacity.
- 9) Solid and pneumatic tires are available; solid tires may incur an upcharge if not included in package.
- 10) Battery weight may vary based on manufacturer.



	Jazzy Select® Traveller	Jazzy Select® Elite	Jazzy Select®	Jazzy Select® 6	Jazzy Select® 6 Ultra	Jazzy Select® 14	Jazzy® 1113 ATS	Jazzy® 600	Jazzy® 614 and 614 HD	Jazzy® 1170 XL Plus	Jazzy® 1420	Jazzy® 1650	
<b>Weight Capacity</b>	300 lbs.	300 lbs.	300 lbs.	300 lbs.	300 lbs.	300 lbs.	300 lbs.	300 lbs.	300 lbs. (HD: 450 lbs.)	500 lbs.	500 lbs.	650 lbs.	
<b>Turning Radius</b> <sup>1</sup>	22.75"	24.75"	20"	20.5"	20.5"	21"	20.5"	20"	20"	26.75"	25.75"	26.25"	
<b>Width</b> <sup>1</sup>	21.5"	22.75"	23.75"	23.5"	23.5"	24.75"	23"	23"	25.125"	30"	27.25"	30.375"	
<b>Length</b> <sup>1,2</sup>	27.75"	34.75"	35.5"	36.625"	36.625"	38"	36"	36.5"	35.5"	45.25"	46"	47"	
<b>Maximum Speed</b> <sup>3</sup>	Up to 3.5 mph	Up to 4 mph	Up to 4 mph	Up to 4 mph	Up to 4 mph	Up to 5 mph	Up to 4 mph	Up to 5 mph	Up to 4.25 mph	Up to 5 mph	Up to 4.5 mph	Up to 5 mph	
<b>Ground Clearance</b> <sup>1</sup>	1.75"	1.5" at anti-tips	1.875" at center frame	2"	2"	3"	2.5"	3"	2.25"	4"	4.5"	4.25"	
<b>Front Wheels</b>	5" solid casters	3" solid anti-tips	5" solid anti-tips	6" solid casters	6" solid casters	6" solid anti-tips	6" solid anti-tips	5" solid OMNI-casters	6" solid casters	8" solid anti-tips	8" solid anti-tips	8" solid anti-tips	
<b>Drive Wheels</b>	8" solid	9" solid	10" solid	10" solid	10" solid	14" solid	10" <sup>9</sup>	14" <sup>9</sup>	14"	16"	16" <sup>9</sup>	16" <sup>9</sup>	
<b>Rear Wheels</b>	3" solid anti-tips	6" solid casters	6" solid casters	6" solid casters	6" solid casters	8" solid casters	8" solid casters	6" solid OMNI-casters	6" solid casters	9" solid casters	9" casters <sup>9</sup>	9" casters <sup>9</sup>	
<b>Drive Train</b>	Two-motor, in-line, rear-wheel drive	Two-motor, in-line, front-wheel drive	Two-motor, in-line, mid-wheel drive	Two-motor, in-line, mid-wheel drive	Two-motor, in-line, mid-wheel drive	Two-motor, mid-wheel drive	Two-motor, mid-wheel drive	Two-motor, Mid-Wheel 6 <sup>®</sup>	Two-motor, Mid-Wheel 6 <sup>®</sup>	Two-motor, mid-wheel drive	Two-motor, mid-wheel drive	Two-motor, in-line mid-wheel drive	
<b>Braking System</b>	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	Regenerative and electro-mechanical	
<b>Suspension Type</b>	Limited	Limited	Active-Trac <sup>®</sup>	Active-Trac <sup>®</sup>	Active-Trac <sup>®</sup>	Limited	Active-Trac <sup>®</sup>	Active-Trac <sup>®</sup> (ATX)	Active-Trac <sup>®</sup> (ATX)	Active-Trac <sup>®</sup>	Active-Trac <sup>®</sup> 4	Active-Trac <sup>®</sup> Limited	
<b>High-Back Seating</b> (max. dimensions)	N/A	20"W x 20"D	20"W x 20"D	20"W x 20"D	20"W x 20"D	20"W x 20"D	20"W x 20"D	600: 22"W x 20"D	614: 22"W x 22"D 614 HD: 24"W x 24"D	28"W x 26"D	24"W x 24"D	32"W x 28"D	
<b>High-Back Seat to Floor Range</b>	N/A	20.5" - 22.5"	19.25" - 21.25"	19.25" - 21.25"	22.75" - 26.75"	23" - 24"	20" - 21.5"	21" - 24"	21.25" - 24.25"	24" - 25.5"	22.5" - 24"	22.75" - 24.25"	
<b>Specialty Seating</b> (max. dimensions)	N/A	N/A	20" x 20"	20" x 20"	N/A	20"W x 20"D	20"W x 18"D	20"W x 20"D	N/A	N/A	N/A	N/A	
<b>Specialty Seat to Floor Range</b>	N/A	N/A	16.5" - 18.5"	16.5" - 18.5"	N/A	18.5" - 19.5"	14.75" - 16.5"	17" - 20"	N/A	N/A	N/A	N/A	
<b>Synergy<sup>®</sup> Seating</b> (max. dimensions)	N/A	N/A	20" x 20"	20" x 20"	N/A	20" x 20"	20"W x 18"D	20"W x 20"D	22"W x 22"D HD: 24"W x 24"D	N/A	24"W x 24"D	32"W x 28"D	
<b>Synergy<sup>®</sup> Seat to Floor Range</b>	N/A	N/A	16.5" - 18.5"	16.5" - 18.5"	N/A	18.375" - 19.375"	15.125" - 17.125"	17" - 19"	17.75" - 19.75"	N/A	18.125" - 20.125"	18.375" - 20.375"	
<b>(without TRU-Balance<sup>®</sup>) Power Elevating Seat Option</b>	N/A	N/A	N/A	N/A	Standard	N/A	N/A	N/A	N/A	N/A	Yes	N/A	
<b>TRU-Balance<sup>®</sup> Power Positioning</b>	N/A	N/A	N/A	N/A	N/A	N/A	Tilt or Recline <sup>8</sup>	Tilt only	N/A	N/A	N/A	N/A	
<b>Specialty Controls</b>	N/A	N/A	N/A	N/A	N/A	N/A	Yes	Yes	N/A	Yes	Yes	Yes	
<b>Standard Electronics</b>	40A, PG GC2	40A, PG GC2	40A, PG GC3	40A, PG GC3	40A, PG 6-key VR2	60A, Dynamic	50A, PG VSI	60A, PG VR2	50A, Dynamic	70A, PG VSI	70A, PG VR2	100A, PG Remote Plus	
<b>Battery Size</b> (2 required)	12 volt, U-1	12 volt, U-1	12 volt, U-1	12 volt, U-1	12 volt, U-1	12 volt, NF-22	12 volt, U-1	12 volt, NF-22	12 volt, NF-22	12 volt, Group 24	12 volt, Group 24	12 volt, Group 24	
<b>Standard Battery Charger</b>	3A, off-board	3A, off-board	3A, off-board	3A, off-board	3A, off-board	5A, off-board	4A, on-board	4A, on-board, standard 5A off-board, optional	5A, off-board	5A, off-board	8A, off-board	8A, off-board	
<b>Per Charge Range</b> <sup>3,7</sup>	Up to 15 miles	Up to 15 miles	Up to 15 miles	Up to 15 miles	Up to 15 miles	Up to 15 miles	Up to 15 miles	Up to 20 miles	Up to 16 miles (HD: 11)	Up to 15 miles	Up to 20 miles	Up to 15 miles	
<b>Battery Weight</b> <sup>10</sup>	24.5 lbs. each	24.5 lbs. each	24.5 lbs. each	24.5 lbs. each	24.5 lbs. each	38 lbs. each	24.5 lbs. each	38 lbs. each	38 lbs. each	53.5 lbs. each	53.5 lbs. each	53.5 lbs. each	
<b>Base Weight</b> <sup>5</sup>	70 lbs.	68.5 lbs.	99 lbs.	100 lbs.	114 lbs.	105 lbs.	77 lbs.	127 lbs.	121.5 lbs.	149.5 lbs.	141.5 lbs.	176 lbs.	
<b>Std. Seat Weight</b>	30 lbs. (contour)	43.5 lbs. (comfort high-back)	37 lbs. (medium-back) <sup>6</sup>	37 lbs. (medium-back) <sup>6</sup>	37 lbs. (medium-back) <sup>6</sup>	37 lbs. (medium-back) <sup>6</sup>	37 lbs. (medium-back)	37 lbs. (medium-back) <sup>6</sup>	37 lbs. (medium-back) <sup>6</sup> HD: 48 lbs. (high-back)	58 lbs. (high-back)	37 lbs. (medium-back) <sup>6</sup>	75 lbs. (high-back)	
<b>Std. Seat Size</b>	18" x 16"	18" x 18"	18" x 18"	18" x 18"	18" x 18"	18" x 18"	18" x 18"	18" x 18"	18" x 18" / 20" x 20-18"	26" x 20"	22" x 20"	24" x 20"	
<b>Warranty</b>	5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors	5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors	5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors	5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors	5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors	5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors	5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors	Lifetime on frame; 2-year on electronics; 18-months on motor gearbox	Lifetime on frame; 2-year on electronics; 18-months on motor gearbox	5-year limited on frame; 1-year limited on electronics; 1-year limited on drive motors	Lifetime on frame; 2-year on electronics; 18-months on motor gearbox	Lifetime on frame; 2-year on electronics; 18-months on motor gearbox	Lifetime on frame; 2-year on electronics; 18-months on motor gearbox

(US) 800-800-8586  
(Canada) 888-570-1113  
www.pridemobility.com

